

Smerigliatrici pneumatiche

NUOVO

- 0,25 - 0,30 kW.
- Carcassa in composito.
- Contiene: pinze da 6 mm e 1/4" incluse.

Accessori: **LG1-K284**
(CPN: 80152119), tubo scarico.

- 335SC4A** - 35 000 giri/min
- 330SC4A** - 30 000 giri/min
- 325SC4A** - 25 000 giri/min

Solo 0,4 kg e 166 mm.



- 330XC4A** - 30 000 giri/min
- 325XC4A** - 25 000 giri/min

Solo 0,6 kg.



- 320AC4A** - 20 000 giri/min
- 314AC4A** - 14 000 giri/min
- 312AC4A** - 12 000 giri/min

Solo 0,55 kg e 170 mm.



NUOVO

5108MAX

- 0,30 kW.
- 25 000 giri/min.
- Solo 0,46 kg e 172 mm.
- Carcassa in composito.
- Contiene: pinze da 6 mm e 1/4" incluse.



308B

- 0,25 kW.
- 25 000 giri/min.
- Solo 0,46 kg e 172 mm.
- Contiene: pinze da 6 mm e 1/4" incluse.



307B

- 0,19 kW.
- 28 000 giri/min.
- Solo 0,33 kg e 125 mm.
- Contiene: pinze da 6 mm e 1/4" incluse.



5102MAX

- 0,30 kW.
- 20 000 giri/min.
- Solo 0,64 kg e 178 mm.
- Carcassa in composito.
- Contiene: pinze da 6 mm e 1/4" incluse.



302B

- 0,25 kW.
- 20 000 giri/min.
- Solo 0,58 kg e 175 mm.
- Contiene: pinze da 6 mm e 1/4" incluse.



301B

- 0,19 kW.
- 21 000 giri/min.
- Solo 0,46 kg e 128 mm.
- Contiene: pinze da 6 mm e 1/4" incluse.



LA429-EU

- 0,42 kW.
- 20 000 giri/min.
- Solo 0,54 kg.
- Contiene: 10 mole.



Pinze di ricambio:



301-700B

Pinze di ricambio (Erickson) per 3...C4A

| | | |
|---|----------|--------|
| DG110-700-G2 | 03641743 | Ø 1/8" |
| DG110-700-6MM | 04261053 | Ø 6 mm |
| DG110-700-G4 | 03641602 | Ø 1/4" |
| Pinze di ricambio per 301B, 302B, 307B, 308B, 5102MAX, 5108MAX e LA429-EU | | |
| 301-700C | 80128952 | Ø 1/8" |
| 301-700B | 04552600 | Ø 6 mm |
| 301-700 | 80102346 | Ø 1/4" |

Caratteristiche a 6,2 bar

| | CPN | | kW | giri/min | kg | mm | AIR NPTF | AIR mm | L/s | Max L/s | dB(A) | m/s ² / K(1) |
|---------------------------------|----------|------------|------|----------|------|-----|----------|--------|-----|---------|-------|-------------------------|
| Smerigliatrici diritte | | | | | | | | | | | | |
| 335SC4A | 45763489 | 6mm + 1/4" | 0,28 | 35 000 | 0,40 | 166 | 1/4" | 10 | 3,8 | 14,2 | 78,4 | 3,0 / 0,8 |
| 330SC4A | 45762390 | 6mm + 1/4" | 0,25 | 30 000 | 0,40 | 166 | 1/4" | 10 | 3,8 | 14,2 | 77,2 | 3,8 / 1,9 |
| 330XC4A | 45763547 | 6mm + 1/4" | 0,25 | 30 000 | 0,62 | 244 | 1/4" | 10 | 3,8 | 14,2 | 80,2 | < 2,5 |
| 325SC4A | 45752366 | 6mm + 1/4" | 0,30 | 25 000 | 0,40 | 166 | 1/4" | 10 | 3,8 | 15,1 | 78,6 | 2,6 / 1,1 |
| 325XC4A | 45763521 | 6mm + 1/4" | 0,30 | 25 000 | 0,62 | 244 | 1/4" | 10 | 3,8 | 15,6 | 78,6 | < 2,5 |
| 5108MAX | 48488340 | 6mm + 1/4" | 0,30 | 25 000 | 0,46 | 172 | 1/4" | 10 | 2,8 | 11,8 | 83,3 | 1,8 / 0,8 |
| 308B | 48488332 | 6mm + 1/4" | 0,25 | 25 000 | 0,46 | 172 | 1/4" | 10 | 3,3 | 13,2 | 92,0 | 3,7 / 1,2 |
| 307B | 48488316 | 6mm + 1/4" | 0,19 | 28 000 | 0,33 | 125 | 1/4" | 10 | 2,8 | 11,3 | 83,0 | 4,5 / 1,1 |
| LA429-EU | 01328558 | 3mm + 6mm | 0,42 | 22 000 | 0,54 | 142 | 1/4" | 10 | 1,8 | 9,4 | 91,0 | 3,2 / 1,7 |
| Smerigliatrici ad angolo | | | | | | | | | | | | |
| 320AC4A | 45763471 | 6mm + 1/4" | 0,30 | 20 000 | 0,55 | 170 | 1/4" | 10 | 3,8 | 15,1 | 78,6 | 2,5 / 1,1 |
| 314AC4A | 45763455 | 6mm + 1/4" | 0,25 | 14 000 | 0,55 | 170 | 1/4" | 10 | 3,8 | 14,2 | 80,2 | 3,2 / 0,7 |
| 312AC4A | 45754595 | 6mm + 1/4" | 0,30 | 12 000 | 0,55 | 170 | 1/4" | 10 | 3,8 | 15,1 | 78,6 | 3,4 / 1,0 |
| 5102MAX | 48488357 | 6mm + 1/4" | 0,30 | 20 000 | 0,64 | 180 | 1/4" | 10 | 2,8 | 11,8 | 84,1 | 3,3 / 1,1 |
| 302B | 48488365 | 6mm + 1/4" | 0,25 | 20 000 | 0,58 | 175 | 1/4" | 10 | 2,8 | 10,8 | 90,0 | 5,5 / 1,5 |
| 301B | 48488308 | 6mm + 1/4" | 0,19 | 21 000 | 0,46 | 128 | 1/4" | 10 | 2,8 | 11,3 | 91,8 | 5,9 / 1,0 |

(1) ISO28927 - triassiale: livello di vibrazione / incertezza misurazione.